

GI SERIES

- ID Grinding**
- »General Purpose
 - »Fixed Menu of Specifications
 - »Broad Menu Option

GA/GP-T SERIES

- Cylindrical Grinding Angle and Plain Head**
- »Dual Traverse Wheelhead, X, Z
 - »Compact Footprint
 - »Large Diameter Wheels
 - »High Speed + Accuracy
 - »High Production

GA/GP-FII SERIES

- Cylindrical Grinding Angle and Plain Head**
- »Single Traverse Wheelhead
 - »Work Traverse on "Z" Axis
 - »General Purpose
 - »High Production Large Wheel Available

200 mm
MAX GRIND DIAMETER

200



GI-10N
Length: 5.12"
High Frequency: 1-WS
Max Grind Diameter: ϕ 5.90"

200



GA/GP-24HT
Max Grind Diameter: ϕ 7.87"
Diameter Wheel Class: ϕ 16"
Wheel Capacity: ϕ 16"
Wheel Spindle Motor: 20 hp

200



GA/GP-25T
Max Grind Diameter: ϕ 7.87"
Diameter Wheel Class: ϕ 20"
Wheel Capacity: ϕ 20"
Wheel Spindle Motor: 10 hp
(Opt. 15 hp, 20 hp)

200



GA/GP-26T
Max Grind Diameter: ϕ 7.87"
Diameter Wheel Class: ϕ 24"
Wheel Capacity: ϕ 24"
Wheel Spindle Motor: 10 hp
(Opt. 15 hp, 20 hp)

300 mm
MAX GRIND DIAMETER

300



GI-20N
Diameter: ϕ 0.20" - ϕ 11.81"
Length: 5.12"-11.81"
High Frequency:
1-WS, 2-WS, 4-WS

300



GA/GP-34-FII
Max Grind Diameter: ϕ 11.81"
Diameter Wheel Class: ϕ 18"
Wheel Capacity: ϕ 18"
Wheel Spindle Motor: 10 hp

300



GA/GP-36-FII
Max Grind Diameter: ϕ 11.81"
Diameter Wheel Class: ϕ 24"
Wheel Capacity: ϕ 24"
Wheel Spindle Motor: 20 hp (Opt. 30 hp)

400 mm
MAX GRIND DIAMETER

400



GA/GP-44-FII
Max Grind Diameter: ϕ 15.75"
Diameter Wheel Class: ϕ 18"
Wheel Capacity: ϕ 18"
Wheel Spindle Motor: 10 hp

400



GA/GP-47-FII
Max Grind Diameter: ϕ 15.75"
Diameter Wheel Class: ϕ 30"
Wheel Capacity: ϕ 30"
Wheel Spindle Motor: 20 hp (Opt. 30 hp)